



CHENGDE JP TECHNOLOGY CO., LTD

D609, FLOOR 6, TECHNOLOGY AND INNOVATION CENTER, HIGH-TECH INDUSTRIAL DEVELOPMENT ZONE, CHENGDE 067000, HEBEI, CHINA; Web: www.smartlifetech.net

TEL/Whatsapp: 86-19910326800; Email: jessie.gao@smartlifetech.net; Wechat: 19910326800

Heating Thermostat Brochure



2025



Whatsapp



WiFi App QR




WiFi App QR

Heating Thermostat Catalogue

Heating Thermostat Products

P/N	Picture		Description
FC285		WiFi heating thermostat (temperature & humidity display)	Measure range: 0 ~ 50 Celsius Temperature control Accuracy : ± 0.5 Celsius Power supply: 90-240VAC (24V optional) Child lock, Open window detect, Frost or overheat protection Sensor type: NTC 10K Weekly programme (5+2/6+1/7) Output: 3A (water heating) / 20A (electric heating) White or black color optional Wi-Fi function, Modbus RS485 optional Power supply: 90-240VAC (24V optional) White or black color for choice
ST-C28		WiFi heating thermostat	Measure range: 5 ~ 35 Celsius Temperature control Accuracy : ± 0.5 Celsius Power supply: 90-240VAC (24V optional) Child lock, Open window detect, Frost or overheat protection Sensor type: NTC 10K Weekly programme (5+2/6+1/7) Output: 3A (water heating) / 16A (electric heating) White or black color optional Wi-Fi function optional Power supply: 90-240VAC (24V optional) White or black color for choice
ST-C27		WiFi heating thermostat	Measure range: 5 ~ 35 Celsius Temperature control Accuracy : ± 0.5 Celsius Power supply: 90-240VAC (24V optional) Child lock, Open window detect, Frost or overheat protection Sensor type: NTC 10K Weekly programme (5+2/6+1/7) Output: 3A (water heating) / 16A (electric heating) White or black color optional Wi-Fi function optional Power supply: 90-240VAC (24V optional) White or black color for choice
ST-C22		WiFi heating thermostat	Measure range: 0 ~ 40 Celsius Temperature control Accuracy : ± 0.5 Celsius Power supply: 90-240VAC (24V optional) Child lock, Open window detect, Frost or overheat protection Sensor type: NTC 10K Weekly programme (5+2/6+1/7) Output: 3A (water heating) / 16A (electric heating) White or black color for choice Wi-Fi function optional

P/N	Picture		Description
ST-C24		WiFi heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-0.5 Celsius Power supply: 90-240VAC (24V optional) Child lock, Open window detect, Frost or overheat protection Sensor type:NTC 10K Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White or black color for choice Wi-Fi function optional
ST-C15		Heating Thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 85-250VAC (24V optional) Power consumption:<1W Sensor type:NTC 10K Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White or black color for choice
ST-C17		WiFi heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 85-250VAC (24V optional) Power consumption:<1W Sensor type:NTC 10K@25Celsius Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White or black color for choice Wi-Fi function optional
ST-C26		WiFi heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 85-250VAC (24V optional) Power consumption:<1W Sensor type:NTC 10K Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White or black color for choice Wi-Fi function optional
ST-C01BW		Heating thermostat (2AA battery)	Measure range:5 ~ 35 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 2AA battery Power consumption:<1W Sensor type:NTC 10K Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White Color Remote control or wireless optional

P/N	Picture		Description
ST-C06BW		Heating thermostat (2AA battery)	Measure range:5 ~ 35 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 2AA battery Power consumption:<1W Sensor type:NTC 10K Output:3A (water heating) /16A (electric heating) White Color Remote control or wireless optional
ST-C09		Wireless heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 85-250VAC (24V optional) Power consumption:<1W Sensor type:NTC 10K Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White color Wireless heating thermostat
ST-C19		WiFi heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 90-240VAC (24V optional) Child lock, Open window detect, Frost or overheat protection Sensor type:NTC 10K Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White or black color for choice Wi-Fi function optional
ST-C18		WiFi heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 85-250VAC (24V optional) Power consumption:<1W Sensor type:NTC 10K@25Celsius Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White or black color for choice Wi-Fi function optional
ST-C07		Heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 85-250VAC (24V optional) Power consumption:<1W Sensor type:NTC 10K@25Celsius Weekly programme (5+2/6+1/7) Output:3A (water heating) /16A (electric heating) White or black color for choice Body material: Antiflaming PC

P/N	Picture		Description
ST-C03		Heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 85-250VAC (24V optional) Power consumption:<1W Sensor type:NTC 10K@25Celsius Output:3A (water heating) /16A (electric heating) Body material: Antiflaming PC
ST-C06		Heating thermostat	Measure range:0 ~ 30 Celsius Power supply: 220VAC, 50/60Hz Control mode:3A heating Temperature sensor:Inflated film case LED and ON/OFF swich
ST-C12		Heating thermostat	Measure range:0 ~ 40 Celsius Temperature control Accuracy :+/-1 Celsius Power supply: 220VAC 50/60Hz Power consumption:<1W Sensor type:NTC 10K@25Celsius Output:3A (water heating) /16A (electric heating) Body material: Antiflaming PC
Sensor		External sensor	length 1m or 3m or 5m, diameter 1.5mm, NTC 10K, B=3950 or 3380
Note: 1. If have any special requirements or OEM/ODM, please kindly contact us freely. 2. Min order quanlity is 200pcs. 3. Warranty 24 months			